


Male Elbow

BLM

SAE 080202 MS51815



Part No.	Tube O.D D (in)	T Straight Thread Size	T ₁ * NPT Size	d	Width across flat		l	l ₁
					h	H		
BLM 2T - 01N	1/8	5/16 - 24	1/8	2.4	11.1	9.5	15.0	18.3
BLM 3T - 01N	3/16	3/8 - 24	1/8	3.2	11.1	11.1	15.2	15.4
BLM 4T - 01N	1/4	7/16 - 20	1/8	5.2	11.1	14.2	16.5	16.7
BLM 4T - 02N	1/4	7/16 - 20	1/4	5.2	14.2	14.2	20.1	20.2
BLM 4T - 03N	1/4	7/16 - 20	3/8	5.2	19.1	14.2	22.6	22.8
BLM 5T - 01N	5/16	1/2 - 20	1/8	6.0	14.2	15.8	17.5	17.8
BLM 5T - 02N	5/16	1/2 - 20	1/4	6.0	14.2	15.8	19.6	19.8
BLM 6T - 01N	3/8	9/16 - 18	1/8	7.0	14.2	17.4	20.1	20.3
BLM 6T - 02N	3/8	9/16 - 18	1/4	7.0	14.2	17.4	20.1	20.3
BLM 6T - 03N	3/8	9/16 - 18	3/8	7.0	19.1	17.4	22.4	22.6
BLM 6T - 04N	3/8	9/16 - 18	1/2	7.0	22.2	17.4	24.6	24.9
BLM 8T - 02N	1/2	3/4 - 16	1/4	10.7	19.1	22.2	23.9	24.0
BLM 8T - 03N	1/2	3/4 - 16	3/8	10.7	19.1	22.2	23.9	24.0
BLM 8T - 04N	1/2	3/4 - 16	1/2	10.7	22.2	22.2	26.1	26.7
BLM 8T - 06N	1/2	3/4 - 16	3/4	10.7	27.0	22.2	28.2	28.3
BLM 10T - 03N	5/8	7/8 - 14	3/8	12.7	22.2	25.4	27.0	27.2
BLM 10T - 04N	5/8	7/8 - 14	1/2	12.7	22.2	25.4	27.0	27.2
BLM 12T - 04N	3/4	1 1/16 - 12	1/2	16.6	27.0	31.7	31.0	31.2
BLM 12T - 06N	3/4	1 1/16 - 12	3/4	16.6	27.0	31.7	31.0	31.2
BLM 14T - 06N	7/8	1 3/16 - 12	3/4	18.0	33.3	34.9	33.1	33.3
BLM 16T - 06N	1	1 5/16 - 12	3/4	22.2	33.3	38.1	33.2	33.4
BLM 16T - 08N	1	1 5/16 - 12	1	22.2	33.3	38.1	33.2	33.4
BLM 20T - 10N	1 1/4	1 5/8 - 12	1 1/4	27.8	41.2	50.0	37.3	37.4
BLM 24T - 12N	1 1/2	1 7/8 - 12	1 1/2	34.1	47.6	57.2	38.8	39.0
BLM 32T - 16N	2	2 1/2 - 12	2	46.0	63.5	75.0	49.7	49.9

* ISO Tapered Threads are available upon request.