


## Reducer

**BR**

SAE 080123



Part No.	Tube O.D D <sub>1</sub> x D	T Straight Thread Size	d	Width across flat		C	l
				h	H		
BR 6T x 4T	3/8 to 1/4	7/16 - 20	5.2	12.7	14.2	22.4	35.0
BR 8T x 4T	1/2 to 1/4	7/16 - 20	5.2	14.3	14.2	25.4	38.0
BR 8T x 6T	1/2 to 3/8	9/16 - 18	7.0	15.9	17.4	25.4	38.7
BR 10T x 6T	5/8 to 3/8	9/16 - 18	7.0	17.4	17.4	27.7	40.9
BR 10T x 8T	5/8 to 1/2	3/4 - 16	10.7	20.6	22.2	27.7	42.1
BR 12T x 6T	3/4 to 3/8	9/16 - 18	7.0	20.6	17.4	29.5	42.7
BR 12T x 8T	3/4 to 1/2	3/4 - 16	10.7	20.6	22.2	29.5	43.9
BR 12T x 10T	3/4 to 5/8	7/8 - 14	12.7	23.8	25.4	29.5	45.7
BR 14T x 10T	7/8 to 5/8	7/8 - 14	12.7	23.8	25.4	29.5	45.5
BR 16T x 8T	1 to 1/2	3/4 - 16	10.7	27.0	22.2	28.4	44.4
BR 16T x 10T	1 to 5/8	7/8 - 14	12.7	27.0	25.4	28.4	44.7
BR 16T x 12T	1 to 3/4	1 1/16 - 12	16.6	28.6	31.8	28.4	48.0
BR 20T x 16T	1 1/4 to 1	1 5/16 - 12	22.2	34.9	38.1	29.5	47.4
BR 24T x 12T	1 1/2 to 3/4	1 1/16 - 12	16.6	41.3	31.8	31.8	53.3
BR 24T x 16T	1 1/2 to 1	1 5/16 - 12	22.2	41.3	38.1	31.8	51.7
BR 12T x 8T	1 1/2 to 1 1/4	1 5/8 - 12	27.8	47.6	50.0	31.8	51.7

All dimensions are in millimeters unless otherwise specified. Dimensions are for reference only, subject to change.