



## Gasket H-ZGSK



Part No.	ZCR Size	d		D		L	
		mm	in.	mm	in.	mm	in.
H-ZGSK- 2	1/8	2.3	0.09	6.6	0.26	0.5	0.02
H-ZGSK- 4	1/4	5.6	0.22	12.5	0.49	0.8	0.03
H-ZGSK- 8	1/2	11.2	0.44	19.8	0.78		
H-ZGSK-12	3/4	16.8	0.66	29.0	1.14		
H-ZGSK-16	1	22.6	0.89	35.6	1.40		

**Note :** Cannot be used in a gasket retainer assembly.

## Gasket Retainer H-ZGRT



Part No.	ZCR Size	d		D		L	
		mm	in.	mm	in.	mm	in.
H-ZGRT- 4	1/4	5.6	0.22	11.9	0.47	0.8	0.03
H-ZGRT- 8	1/2	11.2	0.44	19.2	0.76		
H-ZGRT-12	3/4	16.8	0.66	28.5	1.12		
H-ZGRT-16	1	22.6	0.89	35.1	1.38		

## Ordering Information for Gasket & Gasket Retainer Assembly

**H**  
HY-LOK Clean

**ZGSK**  
**Product Pattern Designator**  
• ZGSK - Gasket  
• ZGRT - Gasket Retainer Assembly

**8**  
**Gasket Plating Option\***  
• Nil - unplated (standard)  
• SP - with silver plated

**BL**  
**Blind Gasket Option\***  
• Nil - Standard  
• BL - Blind gasket

**316L**  
**Gasket Material Designator**  
• 316L - 316L stainless steel  
• NI - Nickel  
• CU - Copper

**Note**

1. Retainer Material for 316L Stainless Steel, Nickel and Copper gasket Retainer Assemblies are 316L Stainless Steel.
2. '\*' No designator is required for standard gasket e.g. H-ZGSK-8 - 316L
3. For application of Blind Gaskets exceed not a differential pressure rating of 100 psi(6.8 bar)

Designator	ZCR Size
2	1/8
4	1/4
8	1/2
12	3/4
16	1