


# Hy-Lok ZCO O-Ring Face Seal Fittings

## Male Elbow


Converts female NPT thread to ZCO gland.



Part Number	ZCO Size in	P Male NPT Size	d	L	L <sub>1</sub>	L <sub>2</sub>	H Wrench Flat	Working Pressure	
								psig	bar
H-ZCOLM 4- 2N	1/4	1/8"	0.18( 4.57)	0.87(22.10)	0.96(24.38)	0.38( 9.65)	1/2"	10000	680
H-ZCOLM 4- 4N	1/4	1/4"	0.18( 4.57)	1.05(26.67)	0.96(24.38)	0.56(14.22)	1/2"	8000	550
H-ZCOLM 8- 6N	1/2	3/8"	0.38( 9.65)	1.26(32.00)	1.26(32.00)	0.56(14.22)	13/16"	7800	530
H-ZCOLM 8- 8N	1/2	1/2"	0.40(10.16)	1.45(36.83)	1.26(32.00)	0.75(19.05)	13/16"	7700	530
H-ZCOLM12-12N	3/4	3/4"	0.62(15.75)	1.67(42.42)	1.48(37.59)	0.75(19.05)	1-1/4"	7300	500
H-ZCOLM16-16N	1	1"	0.87(22.10)	1.94(49.28)	1.56(39.62)	0.94(23.88)	1-11/16"	5300	360

## SAE/ME Adjustable Elbow


Converts SAE/ME straight thread boss to ZCO gland.



Part Number	ZCO Size in	S Straight Thread Size	d	L	L <sub>1</sub>	L <sub>2</sub>	H Wrench Flat	H <sub>1</sub> Hex Flat	O-ring Uniform size Number	U	Working Pressure	
											psig	bar
H-ZCOSL 4- 4U	1/4	7/16-20	0.18 (4.57)	1.19 (30.23)	0.96 (24.38)	0.39 (9.91)	5/8"	9/16"	-904	0.65"	4500	310
H-ZCOSL 8- 6U	1/2	9/16-18	0.30 (7.62)	1.54 (39.12)	1.33 (33.78)	0.44 (11.18)	1-1/16"	11/16"	-906	0.79"	3600	240
H-ZCOSL 8- 8U	1/2	3/4-16	0.40 (10.16)	1.65 (41.91)	1.33 (33.78)	0.50 (12.7)	1-1/16"	7/8"	-908	1.01"	3600	240
H-ZCOSL12-12U	3/4	1-1/16-12	0.62 (15.75)	2.13 (54.10)	1.53 (38.86)	0.66 (16.76)	1-3/8"	1-1/4"	-912	1.44"	2900	190
H-ZCOSL16-16U	1	1-5/16-12	0.87 (22.10)	2.31 (58.67)	1.72 (43.69)	0.66 (16.76)	1-11/16"	1-1/2"	-916	1.73"	2300	150

## Elbow

Connects ZCO glands.



Part Number	ZCO Size in	d	L	H Wrench Flat	Working Pressure	
					psig	bar
H-ZCOLA- 4	1/4	0.18( 4.57)	0.96(24.38)	1/2"	14300	980
H-ZCOLA- 8	1/2	0.40(10.16)	1.26(32.00)	13/16"	11100	760
H-ZCOLA-12	3/4	0.62(15.75)	1.48(37.59)	1-1/4"	10900	750
H-ZCOLA-16	1	0.87(22.10)	1.56(39.62)	1-11/16"	8800	600